

BUILT-IN, STREAMLINED I/O



GLOBAL HEADQUARTERS

59 South State Avenue
Indianapolis, Indiana 46201
P 317-916-4274
F 317-639-4279
TF 877-665-5666
www.hornerautomation.com
sales@heapg.com

INTERNATIONAL OPERATIONS

HORNER EUROPE

Horner Ireland Limited, Unit 1
Centrepark, Centrepark Road
Cork, Ireland
P +353-21-4321266
F +353-21-4321826
info@horner-apg.com
www.hornerautomation.eu

HORNER CANADA

916 42 Avenue SE #120
Calgary, Alberta T2G 1Z2
P (403) 444-0928
F (403) 265-0966
info@hornercanada.com
www.hornerautomation.com

HORNER INDIA

Vaishnavi, No. 3, Domlur 2nd Stage
3rd Phase, Domlur Main Rd.
Bangalore 560071
Karnataka, India
P +91-80-41263460 / 61 / 62
F +91-80-41263464
info@hornerautomation.in

HORNER AUSTRALIA

Unit 15
104 Ferntree Gully Road
Oakleigh Victoria 3166
P 03 9544 0733
F 03 9544 0977
sales@networkautomation.com.au

HORNER CHINA

Sales and Tech Support for China
Room 1001, Nongke Building
No. 268, Baidilu Road, Nankai District
Tianjin 300192, P.R. China
P +86-022-23367571/23360759
F +86-022-23662715
info@hornerchina.com.cn
www.hornerchina.com.cn

INDUSTRY LEADING ALL-IN-ONE CONTROLLER

Our Micro OCS line of products introduces a series of fixed I/O controllers with exceptional performance and a streamlined ordering and pricing structure. These powerful and efficient controllers are well-suited to perform many of the same high-end applications as our popular XL series at the price point of an introductory component - value engineering hard at work.

With proven success across a wide variety of applications, the Micro OCS series is ideal for:

- Custom OEM products
- Power management & back-up generation
- Semiconductor applications
- Packaging machinery
- Water treatment
- Compressor control
- Pump control
- Food processing
- Motion control
- Distributed conveyor control
- HVAC/Environmental control
- Mobile machinery
- Automotive parts manufacturing



The Micro OCS family of products incorporates a similar all-in-one construction as with the XL series. By providing a fixed array of I/O, however, the Micro OCS Series provides a streamlined approach to the market. Applications that do not require the power of the XL products are perfectly suited to our Micro OCS line of products.

POWERFUL, SECURE CSCAPE PROGRAMMING SOFTWARE

The Micro OCS Series (developed using a single, industry-recognized software platform, Cscape) combines graphical ladder logic programming, operator interface development, I/O configuration and network configuration. The user-friendly interface provides free form and drag & drop editor, as well as more than 100 functions to choose from. In addition to the Cscape Advanced Ladder offering, Cscape also supports the IEC 1131 programming languages.

From the Horner website, hornerautomation.com, download the Cscape software or software updates at no charge. This free service allows you to avoid costly licensing fees while always having the most up-to-date software version.

LOWER COSTS, MORE OPTIONS, EASY-TO-USE

With fully integrated hardware and software, the Micro OCS Series offers easy programming, installation, development and set-up. Our controllers have a small footprint and can easily retrofit into an existing system with little effort. None of our Micro OCS products are limited to their on-board I/O. Many variations of distributed remote I/O, including SmartBlock, SmartStix, and SmartMod can be connected via CsCAN, Ethernet, or Modbus. RTU/Modbus based SmartMod I/O is also a cost-effective means of adding a small amount of analog I/O.

The Micro OCS Series utilizes MicroSD™ Data Storage Memory, ideal for data logging, machine recipes, and application files.

CONNECTIVITY

The Micro OCS Series is designed as a modular system for easy selection and growth; CsCAN (CAN Based) high speed networking and Modbus RTU networking capabilities are standard in both series controllers. Ethernet is standard in our X5 and available as an optional component in our X4. Remote I/O options offer high performance, accurate analog, and easy-to-configure digital only modules. Horner I/O has flexible communication options that easily expand current systems.

BUILT-IN DIGITAL & ANALOG I/O

	DC In	DC Out	Relay Out	HSC In	Pulse Out	Analog Inputs	Analog Outputs
X2A	12	12		4	2	4 (current)	2 (current)
X2R	12	2	6	4	2	4 (current)	2 (current)
X4A	12	12		4	2	4 (current / RTD)	2 (current)**
X4R	12	2	6	4	2	4 (current / RTD)	2 (current)**
X5	4	4		4	2	4 (current / volts)	
X7A	12	12		4	2	4 (current / RTD)	2 (current)**
X7R	12	2	6	4	2	4 (current / RTD)	2 (current)**
X10A	12	12		4	2	4 (current / RTD)	2 (current)**
X10R	12	2	6	4	2	4 (current / RTD)	2 (current)**

*High Speed I/O is shared with DC In and DC Out

**Use of more than 2 RTD Inputs negates the ability to utilize Analog Outputs




MICRO OCS SERIES



**FIXED/STANDARD I/O,
EXCEPTIONAL PERFORMANCE**

MICRO SERIES



FEATURES		X2	X4	X5	X7	X10
Controller	Ladder Logic Memory	256 kB	256 kB	1 MB	256 kB	256 kB
	Logic Scan Rate	1.2 mS/K	0.4 mS/K	0.04 mS/K	0.4 mS/K	0.4 mS/K
	Removable Memory	microSD	microSD	microSD	microSD	microSD
	Real Time Clock	Yes	Yes	Yes	Yes	Yes
	Floating Point Support	Yes (32-bit)	Yes (32-bit)	Yes (64-bit)	Yes (32-bit)	Yes (32-bit)
Operator Interface	AutoTune PID Loops	Yes (4 loops)	Yes (4 loops)	Yes (64 loops)	Yes (4 loops)	Yes (4 loops)
	Resolution	128 x 64	480 x 272	480 x 272	800 x 480	1024 x 600
	Display Technology	LCD with LED Monochrome	LCD with LED 350 nits	LCD with LED 450 nits	LCD with LED 300 nits	LCD with LED 300 nits
	Number of Pages	250	250	1023	250	250
	Fields or Objects per Page	15	100	1023	100	100
	Total Keys / Function Keys	20 / 10	5 (on screen) / 4 (on screen)	5 (on screen) / 4 (on screen)	5 (on screen) / 4 (on screen)	5 (on screen) / 4 (on screen)
	Built-In Storage	16 MB	16 MB	128 MB	16 MB	16 MB
	Built-In I/O points	Model A - 30 Model R - 26	Model A - 30 Model R - 26	12	Model A - 30 Model R - 26	Model A - 30 Model R - 26
I/O	High Speed Counter (HSC)	Freq., Pulse, Quad., Total, 10 kHz	Freq., Pulse, Quad., Total, 500 kHz	Advanced, 500 kHz	Freq., Pulse, Quad., Total, 500 kHz	Freq., Pulse, Quad., Total, 500 kHz
	SmartStix, SmartRail, SmartBlock I/O Support	Yes - CsCAN	Yes - CsCAN & Ethernet	Yes - CsCAN & Ethernet	Yes - CsCAN & Ethernet	Yes - CsCAN & Ethernet
	Digital Inputs/Outputs, Max	1024 / 1024	1024 / 1024	2048 / 2048	1024 / 1024	1024 / 1024
	Analog Inputs/Outputs, Max	256 / 256	256 / 256	512 / 512	256 / 256	256 / 256
	General Purpose Registers (words)	5000	5000	8192 (1024 retentive)	5000	5000
	General Purpose Internal Coils (bits)	2048 (retentive 1024)	2048 (retentive 1024)	4096 (2048 retentive)	2048 (retentive 1024)	2048 (retentive 1024)
Ethernet/ Internet	Ethernet Support	No	Standard	Standard	Standard	Standard
	Remote Access	EnvisionRV	WebMI or EnvisionRV	WebMI, HTTP or EnvisionRV	WebMI or EnvisionRV	WebMI or EnvisionRV
	Remote File Access	EnvisionFX	FTP or EnvisionFX	FTP or EnvisionFX	FTP or EnvisionFX	FTP or EnvisionFX
	WebMI Compatibility*	No	Yes - 2 Connections	Yes - 4 Connections	Yes - 2 Connections	Yes - 2 Connections
Serial Communications	RS-232 Ports/RS-485 Ports on shared connector	1 x RS-232 and 1 x RS-485	1 x RS-232 and 1 x RS-485	1 x RS-232 and 1 x RS-485	1 x RS-232 and 1 x RS-485	1 x RS-232 and 1 x RS-485
	PLC/Drive Protocols	Limited	Limited	Yes	Limited	Limited
	RTU/Modbus Master/Slave/Serial ASCII In/Out	Yes	Yes	Yes	Yes	Yes
	USB Port A	No	No	Yes (flash or hard drive support)	No	No
	USB Port Mini-B	Programming Only	Programming Only	Programming Only	Programming Only	Programming Only
CAN Networking	Integrated CsCAN Network	Standard	Standard	Standard	Standard	Standard
	Programming Over Network	Yes	Yes	Yes	Yes	Yes
	Peer-to-Peer Messaging	Yes	Yes	Yes	Yes	Yes
Physical Specifications	Height (inches/mm)	4.92" / 125 mm	3.79" / 96 mm	3.79" / 96 mm	5.65" / 143.50 mm	6.5" / 166.2 mm
	Width (inches/mm)	3.78" / 96 mm	4.92" / 125 mm	4.92" / 125 mm	7.33" / 186.08 mm	10.4" / 263.9 mm
	Overall Depth (inches/mm)	1.41" / 35.8 mm	1.41" / 35.8 mm	1.41" / 35.8 mm	2.08" / 52.88 mm	2.2" / 55.8 mm
	Operating Temperature	-10° to 60°C	-10° to 60°C	-10° to 60°C	-10° to 60°C	-10° to 60°C
Operating Specifications & Standards	Humidity (non-condensing)	5 to 95%	5 to 95%	5 to 95%	5 to 95%	5 to 95%
	Voltage	24 +/- 20% VDC	24 +/- 20% VDC	10-30 VDC	24 +/- 20% VDC	10-30 VDC
	Environmental Rating	IP66, UL Type 3R, 4, 4x, 12, 12k, 13**	IP66, UL Type 3R, 4, 4x, 12, 12k, 13**	IP66, UL Type 3R, 4, 4x, 12, 12k, 13**	IP66, UL Type 3R, 4, 4x, 12, 12k, 13**	IP66, UL Type 3R, 4, 4x, 12, 12k, 13**

*Licensed option
 **For UL and CE Standards, visit the specific product pages for these items on website.